

SP-CHG

Sensplorer Battery Charger Module

WALL MOUNT PANELS HAVE BATTERY

Some of Sensplorer Base Module installed with wall mount panels which has an in-built battery and charger module. It provides a redundant power supply for Sensplorer modules.



- Wall Mount Panel with Battery is used for the following Sensplorer Base Modules:
 - SP-BS1 Sensplorer v3.0
 - SPx-B0808 Sensplorer-M
 - SPx-B0404 Sensplorer-S
- It provides power redundancy for wall mount Sensplorer systems

The Sensplorer Battery Charger Module is used in the Sensplorer Wall Mount Panels. In general this type of installation is preferred in location with no 19" rack mount available.

The battery charger module uses a single 7.0 Ah Sealed Lead-Acid battery.

Technical Specifications

Battery Charger Module

Power	: 12V DC
Working Temp.	: 0 °C / +70 °C
Storage Temp	: -40 °C / +85 °C
Installation	: DIN Rail /Wall Mount
Dimension (W*L*D)	: 158 x 86 x 60 mm

GOING GREEN

Sensplorer helps you to run an environmentally conscious operation



Please let us know about your requests, questions, comments and suggestions...

www.sensplorer.com

MEG

ELEKTRIK-ELEKTRONIK

Resitpaşa mah.Katar cad. İTÜ ARI-1
Teknokent No:2/5/4
34467 SARIYER
İSTANBUL-TURKEY
www.meg.com.tr



SENSPLORER
ENVIRONMENT CONTROL SYSTEM